



## Refrigerators

CCTOS 482WHN

### GALVENĀS FUNKCIJAS

Product name / Commercial code	CCTOS 482WHN
Product code	34004507
EAN Code	8059019021249
Built-in / Free standing	Free-standing
Product category	Refrigerator
Product type	One - door table top
Cooling technology	
Display	

### TEHNISKĀS FUNKCIJAS

Antibacterial function	
Approval certificates	CE
Cat. Dir. 94/2/CE	1Refrigerators without low temperature compartment
Chiller - Fresh zone	
Condensatore	Internal
Defrost process freezer section	Manual
Defrost process fridge section	Manual
Gasket	

Multiflow column	
Plug type	Schuko
Connectivity	None
My Zone	
Humidity Zone	
Dry Zone	
Antioxidant Zone	
ABT	
T-ABT	
Fresher Sensor	
Fresher Shield	
Fresher Pad	
Switch Zone	
Instant Cool Box	
Frequency (Hz)	50
Number of compressors	1
Current (A)	0.40
Voltage (V)	220-240
	DISPLAY
Control interface position	
Control interface	
Door opened indicator - fridge	
Holiday	
Lock	
Smart cool	
Super Cooling Function	
Super freezing	
Temperature adjustable	Refrigerator
	DIZAINS
Bottle holders	
Door shelves material	
Door shelves	

Telescopic guide	
Handles	Comfortable external handle
Ice Maker	
Light	
Number of crispers	
Number of egg racks	
Number of iceholder trays	
Reversible Door	
Shelves finishing	
Shelves for Bottles	
Total number of door shelves	
Direct Access Drawer	
Day Light	
Auto Ice Maker	
Interior ventilator fridge section	No
Material of the shelves	GLASS
Number of Adjustable Shelves in fridge compartment	3
Number of freezing drawers	0
Color of the body	White
Door hinge	Right-mounted
JAUDA UN PATĒRIŅŠ	
Climate class	N-ST
Energy consumption (kWh)	0,308
Energy efficiency class - NEW (2010/30/EC)	A+
Freezer Net capacity (l) ****	0
Freezing capacity (kg)	0
Refrigerator Net capacity (l)	87
Storage Period in Event of Power Failure (h)	
Annual energy consumption	112
Freezer Gross capacity (l)	0

Noise level (dB(A))	42
Refrigerator Gross capacity (l)	92
Star rating	No
Total Unit Net capacity (l)	87
	IZMĒRI
Gross weight (kg)	24
Net weight (kg)	22
Height of the product	840
Product Width (mm)	480
Depth (mm)	500